

## Standard Equipped

Automatic air bleeding mechanism\*AC Voltmeter\*DC Output\*AC Circuit Breakers\*DC Fuse Protection\*Full-power Switch on Dual Voltage\*Extra Large Fuel Tank with FuelGauge\*Large Capacity Silent Muffler

## Optional Equipped

\*Low Oil Shut Down\*4-wheel Kit\*Electric Starter\*Battery\*Remote start function

**CL:**Large Fuel Tank/Control Panel\* **CX:**Large fuel tank / Control Panel / Low Oil Shut Down\*

**E:**Electric Start\* **W:**Welding Generator

## Specification

Model	HL4000CL/HL4000CLE/HL4000CX/HL4000CXE
Rated Frequency [Hz]	50/60
Rated Output [KVA]	2.8/2.0
Max. Output [KVA]	3.0/3.3
Rated Voltage [V]	110,120,220,230,240,110/220,120/240
Rated Rotation Speed [rpm]	3000/3600
Phase Number	Single Phase
Power Factor [cosΦ]	1.0
Excitation	Brushless,Self-Excitation
DC Output	12V/8.3A
Dry Weight [kg]	64(68*)
Dimension: L×W×H [mm]	690×455×545
Engine Model	HL178FAG3(HL178FAG3E*)
Displacement [cc]	306
Bore × Stroke [mm (in.)]	78×64(3.07×2.52)
Continuous Output [hp]	5.0 / 5.5
Starting System	Recoil or Recoil/Electric
Fuel Tank Capacity [L]	12.5
Lubricating Oil Capacity [L]	1.1
Low Oil Pressure Alarm System	CL(E): Without / CX(E): With

**(\*) means: Electric Starter**

