

Standard Equipped

*Automatic air bleeding mechanism*DC Output*AC/DC Circuit Breakers*Full-power Switch on Dual Voltage*Extra Large Fuel Tank with Fuel Gauge*Large Capacity Silent Muffler*Low Oil Warning and Automatic Stop System*4-wheel Kit*Electric Starter*Battery*

Specification

Model	HL5000SE
Type	Brushless, Self-exciting, 2-poles, Single phase
Voltage Regulator	Condenser type
Rated Frequency [Hz]	4.2/4.5
Rated Output [KVA]	4.5/4.8
Max. Output [KVA]	3.0/3.3
Rated Voltage [V]	110,120,220,230,240,110/220,120/240
Power Factor [cosΦ]	1.0
DC Output	12V/8.3A
Over current protector	Fuseless circuit breaker
Dry Weight [kg]	165
Dimension: L×W×H [mm]	920×530×740
Engine Model	HL186FAG3E*
Displacement [cc]	418
Bore × Stroke [mm (in.)]	86×72(3.39×2.83)
Continuous Output [hp]	7.7 / 8.6
Starting System	Electric
Fuel Tank Capacity [L]	14
Lubricating Oil Capacity [L]	1.65
Noise level(Rated at 7m)	70DBA/71DBA